



Introduction

The Atлона **AT-HDVS-200-TX** is a 3×1 switcher with display control for HDMI and VGA transmission over Ethernet-enabled HDBaseT™. It features two HDMI inputs and a VGA input with 3.5mm audio connector. The AT-HDVS-200-TX combines the benefits of a switcher with built-in auto-switching and the advantages of extended-distance HDBaseT signal transmission over a single cable. HDMI signals up to 4K/UHD @ 60Hz with embedded audio, VGA input signals up to 1920x1200, and control signals can be extended up to 330 feet (100 meters). The switcher enables automatic display on/off, auto-switching, third-party control, plus other control features. The switcher receives power from the AT-HDVS-200-RX scaler receiver via Power over Ethernet and together they create a standalone AV switching system with scaling for classrooms and huddle rooms. HDVS-200 series devices are also useful as components in larger systems utilizing switchers such as the AT-UHD-CLSO-824 matrix switcher where they are used as input/output modules. Button pushes are transmitted via IP to any IP based control system or IP controllable device. When used with the AT-HDVS-200-RX, IP commands are converted to RS-232 or CEC commands for use with most displays.

The Atлона **AT-HDVS-200-TX-PSK** is identical to the AT-HDVS-200-TX, with the addition of an external power supply. This makes it ideal for extending AV and control directly to a projector with an HDBaseT input. The AT-HDVS-200-TX-PSK can serve as the central component of a small, automated AV system through automatic input selection, and by sending RS-232 or Ethernet control commands to the projector. With automatic display control capability, the AT-HDVS-200-TX-PSK can power the projector on or off whenever a source is connected or disconnected from the unit.

Applications

- Simple yet complete AV systems with HDBaseT-equipped projectors and flat-panel displays.
- Installations in which HDVS-200 Series transmitters are to be used with third-party HDBaseT devices.

Key Features

3x1 HDBaseT switcher

- Features two HDMI inputs plus a VGA input with 3.5mm audio connector.⁽¹⁾
- Allows advanced HDMI display devices to be used with legacy VGA sources.

Ethernet enabled, HDBaseT extension

- Transmits IP and HDMI signals up to 330 feet (100 meters) @ 1080p and 330 feet (100 meters) @ 4K/UHD⁽²⁾ using CAT6a/7 cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

Auto-switching

- Selects active input when sources are connected or if there is a change in source power status.
- Eliminates need for complex control system in small AV systems.

TCP/IP and RS-232 control

- Flexible control options for compatibility with third-party control systems. RS-232 controlled from HDBaseT connection.
- Reduces integration time and costs.

Front panel Input Select button

- Overrides auto-switching when two active sources are present.
- Simple manual control allows presenter to maintain control of AV system.

Auto display control

- Automatically changes projector power state based on active or standby mode of scaler. Control signals transmitted via IP, RS-232, or CEC.
- Eliminates need for complex control system in small AV systems. Enables display and volume control with AT-UHD-CLSO-824. CEC enables control of low-cost consumer displays.

Front panel input selection and on/off controls

- Remotely controls display power state; provides alternate 'Display Mute' mode.
- Eliminates need for manual operation of display or use of IR remote control.

Front panel volume control

- Remotely controls audio volume; provides 'Mute' mode.
- Eliminates need for manual operation of display or use of IR remote control.

Front panel power and input selection status LEDs

- LED indicators provide power and input selection status information.
- Provides easy setup and troubleshooting.

Local AC-powered version of AT-HDVS-200-TX

- Includes external power supply (**AT-HDVS-200-TX-PSK** only) – ideal for point-to-point installations with an HDBaseT-equipped projector.
- Also can be powered via PoE – provides an additional powering option through a compatible Atlona HDBaseT-equipped device, or the AT-PS-POE power injector.

Award-winning 10 year limited product warranty

- Ensures long-term product reliability and performance in commercial and residential systems.
- Specify, purchase, and install with confidence.

Specifications

Video		
Signal	HDMI	
Copy Protection	HDCP 1.4	
Pixel Clock	300 MHz	
UHD/HD/SD	4096x2160@60 ⁽³⁾ /50/30/25/24Hz 3840x2160@60 ⁽³⁾ /50/30/25/24Hz 1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz
VESA All resolutions are 60Hz	2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1280x1024	1280x800 1366x768 1360x768 1152x864 1024x768 800x600 640x480
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	
Color Depth	8-bit, 10-bit, 12-bit	

Audio	
HDMI	PCM 2.0
Bit Depth	up to 24-bit
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz

Ethernet	
Port	1 x RJ45
Standards and Protocols	HTTPS, Telnet, mDNS
Speeds	Local: 10/100/1000 Mbps Over HDBaseT: 10/100 Mbps
Addressing	DHCP, static - selectable through IP & RS-232 commands, and built-in web server

RS-232	
Port	1 x 3-pin captive screw
Use	Pass-through
Baud Rates	2400, 4800, 9600, 19200, 38400, 57600, 115200
Data Flow	Bidirectional

CEC	
Port	1 x HDMI, Type A, 19-pin female
Triggering	RS-232

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN	15	5	30	10
CAT5e	230	70	330	100
CAT6/6a/7	330	100	330	100

Buttons and Indicators	
Buttons: INPUT, VOL, DISPLAY, UP/DN	4 x push buttons, momentary, tact-type
Indicators: PWR, VGA, 1, 2	4 x LED, green

Connectors	
HDMI IN 1	1 - Type A, 19-pin female
HDMI IN 2	1 - Type A, 19-pin female
VGA IN	1 - 15-pin, VESA female
HDBaseT OUT	1 - RJ45
LAN	1 - RJ45
AUDIO IN	1 - 3.6 mm, stereo
RS-232	1 - 3-pin captive screw
FW	1 - micro-USB
DC 48V (PSK only)	1 - 2-pin, captive screw

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +122 °F	0 to +50 °C
Storage Temperature	-4 to +140 °F	-20 to +60 °C
Operating Humidity (RH)	+20 to +90%, non-condensing	

Power	AT-HDVS-200-TX	AT-HDVS-200-TX-PSK
Consumption	30 W (when paired)	30 W (when paired)
Idle Consumption	N/A	22 W
Supply	N/A	Input: 100 - 240 V AC, 50/60 Hz Output: 48 V DC, 3.125 A
Safety	N/A	CE, FCC, cULus

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.50 x 5.00 x 4.02	38 x 127 x 102
Power Supply (AT-PS-48083-D3) ⁽⁴⁾	1.42 x 1.81 x 4.41	36 x 46 x 112

Weight	Pounds	Kilograms
Device	0.64	0.29

Certification	
Device	CE, RoHS, FCC

Footnotes

- (1) Audio signals will not pass without an accompanying video signal.
- (2) Allows 4K/UHD transmission when used with a compatible HDBaseT receiver.
- (3) 4096×2160@50/60Hz & 3840×2160@50/60Hz supported @ chroma subsampling 4:2:0 8-bit only.
- (4) Only included with AT-HDVS-200-TX-PSK.

Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).