



Introduction

The Atlona **AT-HD-SC-500** is a scaler with built-in 3x1 switcher for HDMI and VGA signals. It features two HDMI inputs and a VGA input with 3.5mm audio connector. The scaler is designed to take video signals from switchers, PCs or laptops and scale them to an HDMI output at a wide-range of HDTV and PC resolutions, up to 1080p/60Hz and WUXGA (1920x1200). For ease of operation, the AT-HD-SC-500 features auto-switching for active input selection when sources are connected or if there is a change in source power status. Input selection can also be controlled from the front panel, RS-232, or TCP/IP commands. Set-up is performed using Atlona's webGUI or OSD. Set-up options include variable preferred input resolutions, output resolution, plus control of brightness, contrast, saturation, hue and sharpness. The AT-HD-SC-500 is ideal for applications where multiple signals with different resolutions must be optimized for a display.

Applications

- Complete system applications**
 The HD-SC-500 provides a compact, yet comprehensive and cost-effective system integration solution with automatic input selection, display control capabilities, and essential audio processing.
- Expanding system capabilities**
 The HD-SC-500 can also be used as an input device on a switcher, matrix switcher, or distribution amplifier that doesn't have a VGA input, and as a dedicated scaler for any device with an HDMI output.

Key Features

3×1 HDMI and VGA video scaler

- Features two HDMI inputs plus a VGA input with 3.5mm audio connector.
- Allows advanced HDMI display devices to be used with legacy VGA sources.

HD video scaler with HDMI output and input resolution control

- Scales output video signals up to 1080p/60Hz and 1920×1200; Choose preferred scaler input resolution from 800×600 to 1920×1200.
- Assures compatibility of VGA and HDMI sources with the display.

Automatic display control using CEC, TCP/IP, or RS-232 commands

- Automatically changes projector power state based on active or standby mode of scaler. Control signals transmitted via CEC, IP or RS-232.
- Eliminates need for complex control system in AV systems. Enables display and volume control. CEC enables control of low-cost consumer displays.

Automatic input selection using video detection technology

- Selects active input when sources are connected or if there is a change in source power status.
- Eliminates need for complex control system in AV systems.

Two HDMI inputs

- Digital inputs to support up to two HDMI sources or DisplayPort and DVI sources with appropriate adapters.
- Ideal for a variety of digital sources including laptops, PCs, and cameras.

One analog input on 15-pin HD connector

- Accepts RGBHV signals using common adaptors and break out cables.
- Provides input options for legacy analog sources.

TCP/IP and RS-232 control

- Flexible control options for compatibility with third-party control systems.
- Reduces integration time and costs.

EDID management

- Manages EDID communications between source and switcher; allows integrators to force a source to a preferred resolution.
- Ensures desired audio formats and video resolutions are provided to the AV system.

HDCP management

- HDCP compliance can be disengaged through AMS, the web GUI, or a control system.
- Allows non-protected material from PCs to pass to non-compliant displays, streaming devices, and teleconference systems; protected content is not transmitted.

Key Features (continued)

Front panel input select button

- Overrides automatic input selection when two active sources are present.
- Simple manual control allows presenter to maintain control of the image on screen.

Front panel display on/off control

- Remotely controls display power state; provides alternate 'Display Mute' mode.
- Eliminates need for manual operation of display or use of IR remote control.

Front panel volume control

- Adjusts level of both embedded and de-embedded audio; provides 'Mute' mode.
- Simplifies audio level settings for best sound.

Audio de-embedding

- De-embeds PCM audio from HDMI inputs to audio output.
- Provides audio signal routing to sound system.

Balanced audio output

- Professional, +4dBu audio is provided on a 5-pin captive screw connector.
- Allows for fast integration with professional sound systems.

Works with AMS

- This IP-controllable product can be remotely managed by the Atlona Management System software.
- Integrates product configuration, management, and updates to reduce installation time and enable remote support.

Included accessories

- User guide, power supply, detachable power cable, captive screw connectors, and mounting brackets.

Specifications

Video	
Signal	Input - HDMI Input - VGA Output - HDMI
Copy Protection	HDCP 1.3
Pixel Clock	225 MHz
HD/SD	1920x1080p@23.98/24/25/29.97/30/50/59.94/60Hz 720x576p 720x576i 1920x1080i@50/59.94/60Hz 720x480p 1280x720p@50/59.94/60Hz 720x480i
VESA All resolutions are 60Hz	1920x1200 1280x1024 1680x1050 1280x800 1600x1200 1152x768 1440x900 1024x768 1400x1050 800x600 1366x768 640x480 1360x768
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0

Audio			
HDMI Pass-Through Formats	PCM 2.0 LPCM 5.1 LPCM 7.1	Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos®	DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Depth	Up to 24 bits		
Analog Audio			
Format	Stereo 2-Channel		
Balanced Output	+4 dBu nominal gain, +20 dB headroom		
Frequency Response	20 Hz to 20 kHz, ± 0.5 dB		
THD+N	< 0.004% at 20 Hz to 20 kHz		
SNR	> 105 dB at 1 kHz, zero clipping @ 0 dBFS, unweighted		
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz		

Control	
RS-232	Device control and configuration Supported baud rates: 2400, 4800, 9600, 19200, 38400, 57600, 115200
IP	Protocols: HTTP, Telnet, mDNS Modes: DHCP, Static - selectable through webGUI
CEC Support	Yes

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10

Buttons and Indicators	
Buttons: INPUT, DISPLAY, VOL UP, VOL DN	4 x momentary, tact-type
Indicators: POWER, VGA 1, 2	4 x LED, green

Connectors	
HDMI IN 1	1 x Type A, 19-pin female
HDMI IN 2	1 x Type A, 19-pin female
VGA IN	1 x HD15, female
HDMI OUT	1 x Type A, 19-pin female
AUDIO IN	1 x 3.5 mm, mini-stereo
AUDIO OUT	1 x 5-pin captive screw, balanced / unbalanced 2-channel
RS-232	1 x 3-pin captive screw
LAN	1 x RJ45, 100Base-T
PWR	1 - 2-pin captive screw

Environmental	Fahrenheit	Celsius
Operating Temperature	+32 to +122	0 to +50
Storage Temperature	-4 to +140	-20 to +60
Operating Humidity (RH)	20% to 90%, non-condensing	

Power	
Consumption	10.4 W
External Power Supply	100 - 240 V AC, 50/60 Hz Output: 5 V / 4 A DC

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.50 x 5.00 x 4.02	38 x 127 x 102
Power Supply (AT-PS-54-C)	1.20 x 2.00 x 3.20	30 x 50 x 81

Weight	Pounds	Kilograms
Device	0.60	0.27

Certification	
Device	CE, FCC
Power Supply	CE, TUV, RCM, RoHS, FCC

Compliance	
NDA-899	Yes

Accessories

SKU	Description
AT-LC-H2H-1M	LinkConnect 1 Meter HDMI to HDMI Cable
AT-LC-H2H-2M	LinkConnect 2 Meter HDMI to HDMI Cable
AT-LC-H2H-3M	LinkConnect 3 Meter HDMI to HDMI Cable

Copyright, Trademark, and Registration

© 2022 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).