



Specifications

Input Ratings	Minimum	Maximum	Nominal
Voltage	90 V AC	264 V AC	100/240 V AC
Current @ 100 V AC / 60 Hz - 240 V AC / 50 Hz full load	---	2.0 A rms	---
Frequency	47 Hz	63 Hz	50/60 Hz

Output Ratings	
Voltage	48 V DC
Current	0 - 0.83 A
Power	39.84 W, max

Protection	
Overvoltage	175% Maximum of rated voltage
Overcurrent	110% ~ 200% @ 100 - 240 V AC input

Temperature	Fahrenheit	Celsius
Operating	+32 to +104	0 to +40
Storage	-4 to +185	-20 to +85
Humidity (Operating)	10% to 90%	
Humidity (Storage)	5% to 90%	

MTBF	
MIL-STD-781C (N.A)	30000 hours

Application	
Environment	Indoor use only

Weight	Pounds	Kilograms
Device	0.66	0.30

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.38 x 4.45 x 1.93	35 x 113 x 49

Certification	
Device	UL, CUL, TUV/GS, CB, CE, FCC, PSE, CCC

Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. “Atlona” and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).